

# DSX® 3000

## Use

Newtonian rheology modifier for aqueous coatings, solvent-free.

## Specification

Appearance	clear light amber liquid
Solids	30 %
Density at 25°C	1.05 g/cm <sup>3</sup>
Viscosity	5,000 mPa·s
VOC (%)	nil

## Properties

DSX 3000 offers advantages over other associative thickeners in:

- excellent flow and leveling
- efficiency in ICI viscosity development
- reduced or eliminated syneresis
- superior scrub resistance
- excellent shelf life for consistent efficiency in performance
- clear non-settling non-separating solution

## Application

Solvent-free coatings for furniture, parquet coatings, stains. Can be combined with other thickeners.

## Dosage

The recommended dosage is between 0.5 - 2.0 % calculated on final formulation.

DSX 3000 can be incorporated at any stage of the production.

## Approvals

BgvV XL

FDA 175.105; 175.300; 175.320; 176.170; 176.180;  
176.200

**Regulatory Status**

DSL/NDSL, TSCA, EINECS, AICS, ENCS/MITI

**Revision-No.**

1-05.2003 Effective May 23, 2003

Subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 2 years.

---

Suggestions of processing and using our products are given with best knowledge and information but without obligation. COGNIS does not accept any guarantee to the suitability of a product for the user's specific purpose. Furtheron the user himself assumes a liability to follow all legal regulations by using our products. The user can only pass on our sample to third parties with previous assent of COGNIS.

